2 VEAR WY Sleek and contemporary snap-open frame LED displays utilize an edge-lit technology to emit a bright, even lit across its entire surface.

- High Quality LED Light Source (Ultra Bright Grade 3528 SMD Technology)
- 50,000 hours lifespan
- Plug-n-Play Exit Barrel
- RoHS Compliant Product

- Frame Snap Open on all sides for easy graphic changes
- Landscape or Portrait Mounting Clips attached
- 1/8" Clear Lense Cover Include with Frame

#### **Applications**

- P.O.P. Displays
- Cabinet and Light Boxes
- Menu Board lighting
- Ceiling, Floor and Wall Lightings
- Decorate lightings

# Lumatek Edge-Lit Snap Frame 22'' x 28'' x 15/16'' Anodize Frame

### ★ Specification

LED Quantity	135 Diodes ( on two long edge )
Consumption	10.80W
Working Current	0.90A
Lumen Flux	878 lm
Lux	1400-1800
Panel Thickness	0.20" (5mm)
Operating Voltage	12v DC
UL Power Adapter Included	24 Watt

# ★ Environmental

Operating Temperature	-20°c to +60°c
Storage Temperature	-40°c to +85°c
Rating	Indoor Use Only
Frame Housing	Aluminum Anodized
Wire Connection	5.5x2.1mm Barrel
Overall Dimensions	22" x 28" x 15/16" (H x W x D)
Visible Dimensions	20" x 26" ( H x W )
Weight	Pending

CE F©

RoHS

# $\star$ Mechanical

ESTEE LAUDER

ESTEE LAUDER





© 2011 MaxBrite LED Lighting Technology - 1740-B Junction Ave. - San Jose, CA 95112 Toll Free: 1-800-297-2210 - Fax: 1-408-437-1602 | www.maxbriteled.com