

T-Printz™ Solvent Fabric Transfer

Designed For Solvent Inkjet Ink Printers



Our new T-Printz™ Solvent Fabric Transfer is extremely thin, durable and provides a long lasting easy to wear a t-shirt or imprinted fabrics. To achieve best results with T-Printz Solvent Fabric Transfer follow detailed instructions below. Test a swatch in advance of any production run to ensure T-Printz applies as desired. When applying T-Printz™ to polyester blends, adjust heat slightly lower depending on higher than 50% polyester content in the fabric.

Printers:

Eco/Mild/Mid/Hot Solvent

EPSON® GS-6000

Hewlett-Packard® 8000, 9000, 10,000

Roland® - VP, XC,AJ

Mutoh® - Valuejet

Mimaki® - JV-33, JV-3, CJV

Fabric Transfer or Generic Vinyl Profile
all heat at 30°C or 86°F

Items Needed:

• Sharp Cutter Blade:

(Vinyl Cutter)

• Application Tape:

Polyester Hot Mask Transfer Product

RTape Conform 4050 or 4000

• Heat Press:

Fabric designed to heat 375°F

Fabric Types:

• 100% Cotton

• 50/50 Poly/Cotton Blends

• All Poly/Cotton Blends

• Reduce heat press
temperature for blends



1) After loading T-Printz in Print/Cut Device ensure cutting blade is sharp and proper force/weight is set. Lower setting substantially from standard vinyl and complete a test cut procedure.

• Ensure blade is sharp. Example shows a new 45° blade. (Left)

2) Print following suggested print settings: "Fabric Transfer or Generic Vinyl Profile All heaters at 30°C or 86°F". (Right)



3) Set temperature on press to 370° - 375°F or 188°C - 190°C (100% Cotton)



4) Set heat press pressure to firm or heavy.



5) Weed unwanted area of image.



How to Buy

For additional Sihl Digital Imaging product information, please call 1-800-366-7393 or visit our website www.sihlusa.com where you can also find an authorized Sihl reseller near you.

T-Printz™ Solvent Fabric Transfer

Designed For Solvent Inkjet Ink Printers



6) Apply application tape over complete image without tiling or creating a seam. For small text (under .75") weed and apply application tape within one hour of cutting. Some curl might occur after one hour due to the thin T-Printz™.



7) Press fabric only for 5-10 seconds to remove any moisture from shirt or fabric.



8) Place image application tape side down and peel back release liner.



9) Place image on fabric centered with no air bubbles.



10) Press fabric and transfer 15-20 seconds. Remove from press and let cool!



11) After cooling peel back release liner at a sharp angle.

Wash Instructions for longest lasting results:

- Wash delicate mode
- Inside out
- Tumble dry light or no heat

Similar Products:

4583 - T-Printz Universal Light Fabric Transfer

4578 - T-Printz Universal Dark Fabric Transfer

Compatible with both for Aqueous and Solvent Inkjet Printers



How to Buy

For additional Sihl Digital Imaging product information, please call 1-800-366-7393 or visit our website www.sihlusa.com where you can also find an authorized Sihl reseller near you.

